





## Central **Water Heaters**

Floor Mounted (Vertical) ~











- Maximum tank working pressure of 150 PSI
- Over-temperature protector cuts off power
- Automatic thermostat keeps water at desired temperature
- Brass drain valve
- Temperature and pressure relief valve included

### Point of Use **Water Heaters**

Wall Mounted ← (Horizontal & Vertical)~









- ❷ Durable Copper Heating Element, Standard Flange Type Connection, Easy For Replacement.
- **Solution** Exclusive Rheem Glass Tank Lining.
- Thermostat Rating 16 amphs, maximum Thermostat Setting 70 Degree Celcius.
- Standard Pressure Relief Valve For Tank Safety.
- Maximum Tank Working Pressure 8 bar.

For attractive offers & schemes, Contact **\ +968 9744 9624** 











# **SUSTAINABLE ENERGY**

**SOLAR POWERED WATER HEATERS** 

# Solar Thermosiphon



### Technical Data

- ✓ Factory Tested at 300PSI (20Bar).
- ⊗ Backup heating elements 1.5 to 3.5KW
- ✓ 10 bars tank and collector pressure.
- **Solution** Reduce carbon footprint, renewable product.
- Collector sizes 2.0 and 2.5 square meters
- High absorption glass and special AR coatings
- Enabling at 840C

#### **Features**

- Single / multiple collectors available
- O Double jacket design (excellent heat dissipation)
- (excellent for extreme climate conditions).
- Standard Base frame 21-35degee, optional 21 and 45 deg.
- Standard RAL 9006 color, optional 9010, Mg, Al, SS304, SS316













Category	Capacity Range(Gal)	kW Range	Volt	Ph/Hz	Certification	Offering
Solar Thermosiphon	200-300L	1.5-3.5	220-240V	1P/50-60	Keymark DCL	RHSA20 RHOA20

For attractive offers & schemes, Contact



**\ +968 9744 9624** 



